

E-4

Residential The Viking E-4™ Swing Gate Operator

CLASS I Vehicular Gate Operator



VIKE-4PKG-SGL

Viking E-4 (Complete Set - ECU + 1 Actuator Arm)

VIKE-4PKG-M/S

Viking E-4 (Complete Set - ECU + 2 Actuator Arms)

VIKE-4 ARM

Viking E-4 (1 Actuator Arm Only)



Viking E-4 ECU Controller



Viking E-4 Arm

Arm: 3.9" W. x 4" H. x 36.4" L.
Control Box: 16" W. x 15.6" H. x 6" D.



#VIKDUBB12

Viking 12V DC Batteries Available
3.5 W. x 4" H. x 2.75" D.



UL325
UL991
Compliant



Operational Specifications

- * Operation: 24 VDC with 1/2 HP Motor
- * Main Power Source: 120/240 VAC Single Phase
- * Battery: 7 AMP Hour 12 VDC x 2
- * **10 ft. Gate - 850 lbs. / 12 ft. Gate - 750 lbs.**
- * **14 ft. Gate - 650 lbs. / 18 ft. Gate - 550 lbs.**
- * Max. Opening Speed: 12-16 Seconds per 90°
- * Operating Angle 135°
- * Fail-Safe / Fail-Secure Option
- * **Battery Back-up: 400 Full Cycles**
- * Max Duty Cycle: 100 % (Continuous Cycles)
- * Temperature: -20° F to + 160° F
- * Plug & Play Connection for Viking Wireless Expansion Products
- * Quick Release Handle for Manually Operating the Gate
- * On-Board Lightning Protection 20,000 volts / 10,000 amps
- * **Limited Factory Warranty: 2 Year Residential**
- * Wt. 55 lbs. Single Arm with Control Box
- * Wt. 87 lbs. Double Arms with Control Box



UL325
UL991
Compliant

**Requires A Monitored UL
Compliant Entrapment
Protection Sensor -**
See Page 16-2

VIKING MONITOR - The Viking Monitor App will wirelessly open/close your gate from anywhere in the world. Security is not a concern since the Viking Monitor Application will give you instant notifications on all gate operations and actions. With one touch you are able to view all history, diagnostics, real time data and more! Save all of your operators data with the Cloud and/or a USB. The Viking Monitor App will easily interface to your Android/iPhone mobile devices with a simple download of the application from your App Store. #VIK-MONITOR



Residential and Commercial

The Viking G-5™ Swing Gate Operator

CLASS I, CLASS II, CLASS III, and CLASS IV Vehicular Gate Operator



VIKG-5PKG-SGL

Viking G-5NX (Complete Set - ECU + 1 Actuator Arm)

VIKG-5PKG-M/S

Viking G-5NX (Complete Set - ECU + 2 Actuator Arms)

VIKG-5NX ARM

Viking G-5 (1 Actuator Arm Only)

Viking G-5 Controller



Viking G-5NX Arm

Arm: 4" W. x 5" H. x 41.75" L.
Control Box: 15" W. x 14" H. x 6-1/2" D.



#VIKDUBB12

Viking 12V DC Batteries Available
3.5 W. x 4" H. x 2.75" D.



UL325
UL991
Compliant



Operational Specifications

- * Operation: 24 VDC with 1/2 HP Motor
- * Main Power Source: 115/230 VAC Single Phase
- * Battery: 7 AMP Hour 12 VDC x 2
- * **10 ft. Gate - 2000 lbs. / 12 ft. Gate - 1500 lbs.**
- * **16 ft. Gate - 1000 lbs. / 18 ft. Gate - 800 lbs.**
- * Max. Opening Speed: 15-18 Seconds per 90°
- * The G-5 will Open Inside to a 120°. Open Outside to a 105°
- * Fail-Safe / Fail-Secure Option
- * **Battery Back-up: 400 Full Cycles (600 lbs. / 12' Gate)**
- * Max Duty Cycle: 100 % (Continuous Cycles)
- * Temperature: -20° F to + 160° F
- * Access Key Release For Manual Operation
- * Built-in Three Push Button Station
- * On-Board Lightning Protection
- * Solar Panel Ready: Requires 24VDC 80 watts
- * **Limited Factory Warranty: 4 Year Res. and 3 Year Com.**
- * Wt. 80 lbs. Single Arm with Control Box
- * Wt. 118 lbs. Double Arms with Control Box

VIKING MONITOR - The Viking Monitor App will wirelessly open/close your gate from anywhere in the world. Security is not a concern since the Viking Monitor Application will give you instant notifications on all gate operations and actions. With one touch you are able to view all history, diagnostics, real time data and more! Save all of your operators data with the Cloud and/or a USB. The Viking Monitor App will easily interface to your Android/iPhone mobile devices with a simple download of the application from your App Store. #VIK-MONITOR

**Requires A Monitored UL
Compliant Entrapment
Protection Sensor -**
See Page 16-2