

18" Bull Point - BP-18S

Designed for Breaking up concrete, brick, asphalt, etc...
Light demolition applications.
Starting holes in concrete slabs.



**Fits All
Spline Drive
Hammer
Drills**

BP-18S

Wt. 2.3 lbs.



RELTON

CORPORATION

**18" Cold Chisel - CC-18S**

Designed for Edging, Chipping and channeling concrete, masonry or brick. Light demolition applications.



**Fits All
Spline Drive
Hammer
Drills**

CC-18S

Wt. 2.3 lbs.



1" Wide

RELTON

CORPORATION

**Rotary-Only Rebar Cutters**

SPECIAL ORDER! 1-2 days lead time.

Non-Removable-Shank Rebar Cutters

Non-removable-shank rebar cutters are sold in diameter and overall lengths. All shank ends are 1/2" in diameter.

Removable-Shank Rebar Cutters

Can be sold as a Complete Set, Cutter Head only, or Shank only. All shanks 1/2" in diameter.

1. When rebar is encountered while drilling with a rotary hammer and a carbide hammer bit, immediately stop the rotary hammer and remove the bit from the hole.
2. Mount a rotary rebar cutter in a standard 1/2" drill motor or 1/2" hammer drill (in the rotary position only); insert the rotary rebar cutter into the hole and drill through the embedded rebar.
3. Remove the rotary rebar cutter after the rebar has been drilled completely through and finish drilling the hole with the rotary hammer and hammer bit.

RELTON

CORPORATION



At last, the answer to drilling through concrete-embedded rebar! No more broken or shattered hammer bits; now you can drill through the rebar and not have to relocate the hole to avoid rebar!
SPECIAL ORDER! 1-2 days lead time.

