



Core Bodies have a 4-1/2" core depth and are machined from solid steel.



Core Bit With Shank

Relton's unique taper design eliminates the breakage problems inherent with threaded systems.

Concrete-Termite Hammer Core Bits

Our Relton Core Bits can be re-sharpened or the carbide teeth replaced to save you money.

Part #	Core Dia.	Core Length	Core Depth	Wt.
CBT-28HO	1-3/4"	6"	4-1/2"	1.8 lbs.
CBT-32HO	2"	6"	4-1/2"	2.4 lbs.
CBT-40HO	2-1/2"	6"	4-1/2"	3.7 lbs.
CBT-44HO	2-3/4"	6"	4-1/2"	4.3 lbs.
CBT-48HO	3"	6"	4-1/2"	4.9 lbs.
CBT-56HO	3-1/2"	6"	4-1/2"	6.3 lbs.
CBT-64HO	4"	6"	4-1/2"	7.8 lbs.
CBT-72HO	4-1/2"	6"	4-1/2"	8.5 lbs.
CBT-80HO	5"	6"	4-1/2"	9.3 lbs.

Shanks For Core Bits



SMXTL-10

10" Drilling Depth
Wt. 1.8 lbs.

SDS-MAX

Other lengths available by special order

Designed to be used with Relton's Hammer Core Bits (above) ranging from 1-3/4" to 5" in diameter. These two shanks alone are able to work with a large variety of heavy duty hammer drills available on the market today. Other specialty shanks can be ordered (while supplies last).



Once Relton's hammer core bit system has been used, the tapered shank cannot be removed by conventional means. For shank removal, the shank can be sent to Relton. Suggestion: Use one shank per core bit and leave together as one unit.

S02TL-10

10" Drilling Depth
Wt. 1.8 lbs.

Spline Drive

Other lengths available by special order

Starter Point

Used With The Hammer Core Bits Above



Starter Point Instructions:

Slide the starter point into the core body (starter point is designed for a loose fit). Drill about a 1/8" deep cut with the starter point in the core body. Remove the starter point from the core body and finish drilling the hole.

Part #	Core Dia.	Wt.
CBSP-28	1-3/4"	0.40 lb.
CBSP-32	2"	0.60 lb.
CBSP-40	2-1/2"	0.60 lb.
CBSP-44	2-3/4"	0.75 lb.
CBSP-48	3"	0.90 lb.
CBSP-56	3-1/2"	0.90 lb.
CBSP-64	4"	0.90 lb.
CBSP-72	4-1/2"	1 lb.
CBSP-80	5"	1.2 lbs.