


VR910-DT/VR914-DT

Vandal ResistantDummy Trim (Models With and Without Black Grip)

- VR910-DTwith black grip, VR914-DTwithout black grip
- Closed pull design eliminates a hooking point to be able to forcibly pull a secured door open
- Ligature resistant design
- Foruse with Von Duprin 98/99 Seriesrim and vertical rod exit device
- Pulloperation only
- Non-handed



Specifications	
Available sizes	11gauge (0.120"thick)
Material substrate	304 Seriesstainless steel standard,exceeding industry standards for corrosion resistance.Recommended for external applications.
Mounting hardware	• Fordoor thickness 1-3/4"-2-1/4" • 10-24 x 1"and 10-24 x 1-1/2"mounting screw size • Can be mounted directly to Von Duprin 98/99 device • Standard mounting - welded studs fasten with pan head screws on opposite side of door • Optional through bolt mounting - bolt through face of trim into device for added security

Dimensions				
Width	Height	Through Bolt Pattern (4 Holes)	Clearance Grip to Door	Projection
5-1/4"	11"	1-3/8" wide x 7" high	1-1/2"	1-7/8"

Finishes			
BHMA	Description	Substrate	Finish
630	Satin stainless	Stainless steel	US32D

Models are available with or without attractive black plastisol edge grip.
Custom finishes are available as engineering special,consult customer service.